

# ***CERTIFICATE***

## ***for Resins***

THIS IS TO CERTIFY that the following RESINS have been found to comply with the specifications established in the American Society for Testing and Materials standard ASTM D6400 and/or D6868 in accordance with the terms and conditions of the "Biodegradable Products Institute – Certification Program for Products Made of Compostable Plastics – Program Rules":

- Bio-Flex® F 6510, a natural resin for making cast films with a maximum thickness of 87 microns [J-00205762]

as further described in the application and related information submitted to the Biodegradable Products Institute by FKUR Kunststoff GmbH Corporation, (the "Licensee") a corporation of Germany.

Specific products associated with these certifications can be found on the BPI Product Catalog: <http://products.bpiworld.org/companies/fkur-kunststoff-gmbh>


This approval is for resins only. Manufacturers of products must seek a separate BPI Certification in order to use the BPI name and trademarks.

This Certificate authorizes the Licensee to use the Certification Program Logo depicted below in relation to such Product (resins only), subject to all conditions and terms of the Program Rules and the License Agreement between the Biodegradable Products Institute and the Licensee.



**COMPOSTABLE**  
IN INDUSTRIAL FACILITIES

Check locally, as these do not exist in many communities. **Not suitable for backyard composting.** CERT # 1437004

By:   
BPI Executive Director

Valid until: March 31, 2019  
Certificate #: 1437004-9

**Products on this Certificate:**

The following item numbers (SKUs) are certified under this document. Only these items are published on the BPI's web-based products catalogs.

The licensee shall inform BPI immediately for any new products or discontinued products. These products were certified under product review J-00205762 and must be recertified by the BPI on or before March 03, 2019.

Brand	Manufacturer SKU	Title
BioFlex®	F 6510	Bio-Flex® F 6510, a natural resin for making cast films with a maximum thickness of 87 microns

